

Share printers without running wires!



The Linksys Wireless-G PrintServer for USB 2.0 lets you connect a USB or parallel printer (or both!) directly to your network, eliminating the need to dedicate a PC to print sharing chores. Using a PrintServer frees up your "print share PC" so you don't have to leave it on all the time. It also removes the printing bottleneck, and sets your PC free to do more useful work.

Connect the PrintServer directly to your network by 10/100 Ethernet cable, or wirelessly over 54Mbps Wireless-G (802.11g). The wireless option lets you put your printers wherever you want to, without having to run cables. Whichever way the PrintServer is attached to your network, both your wireless and wired PCs will have access to it, and the printers it's connected to. And if you don't use wireless for general networking in your office, you can still use the Wireless-G connection in ad-hoc mode to print from visiting Wireless-G and Wireless-B PCs.

The USB port is compatible with USB 1.1 printers, as well as printers that support the new high-speed USB 2.0 specification for even faster throughput. There's also a separate port for a standard parallel printer. For even more versatility, you can connect two printers, one to each port, and send your documents to whichever one is most appropriate for each print job.

A user-friendly Setup Wizard makes installation easy, the compact case fits anywhere, and the three megabyte print buffer size handles even large graphics-intensive print jobs. Let the Linksys Wireless-G PrintServer for USB 2.0 bring efficiency to your printing tasks.

Share up to two printers with everyone on your network -- works with most parallel and USB (1.1 or 2.0) printers

Connects your printers directly to the network by 10/100 wired Ethernet or 54Mbps Wireless-G (802.11g)

No need to dedicate a PC to print server chores

Remotely administered through your web browser, SNMP, or the included utility

Wireless-G PrintServer for USB 2.0

Product Data



Wireless-G

PrintServer for USB 2.0

Features

- Complies with IEEE 802.11g, 802.11b, 802.3 and 1284 standards
- Features both a Parallel port and a high-speed USB 2.0 port that is backward compatible with USB 1.1
- Supports TCP/IP, SMB (Service Message Block), AppleTalk (EtherTalk), and NetBEUI.
- Bi-Admin program makes it easy to configure the Wireless-G Print Server in Windows 98SE, ME, 2000 or XP.
- SNMP management allows users to monitor, configure and troubleshoot using existing SNMP management tools.
- Built-in IPP (Internet Printing Protocol) Server and Windows IPP client, enables printing to your printer from anywhere on the Internet.

Specifications

Model Number	WPS54GU2
Standards	IEEE 802.11g, IEEE 802.11b, IEEE 802.3, IEEE 1284, USB 2.0
Ports	Power, USB, Parallel, LAN
Buttons	Reset
Cabling Type	USB 2.0, UTP CAT5, DB25 Parallel
LEDs	Status, LAN, WLAN, Parallel, USB
Security Features	WEP
WEP key bits	64, 128

Environmental

Dimensions W x H x D	4.13" x 5.31" x 1.18" (105 mm x 135 mm x 30 mm)
Unit Weight	7.05 oz. (0.2 kg)
Power	12V 1A
Certifications	FCC, IC-03
Operating Temp.	32°F to 104°F (0°C to 40°C)
Storage Temp.	-4°F to 128°F (-20°C to 70°C)
Operating Humidity	10% to 85% Non-Condensing
Storage Humidity	5% to 90% Non-Condensing

Linksys
A Division of Cisco Systems, Inc.
18582 Teller Avenue
Irvine, CA 92612 USA

E-mail: sales@linksys.com
support@linksys.com

Web: <http://www.linksys.com>

Linksys products are available in more than 50 countries, supported by 12 Linksys Regional Offices throughout the world. For a complete list of local Linksys Sales and Technical Support contacts, visit our Worldwide Web Site at www.linksys.com.

Minimum Requirements

- 200 Mhz or Faster Processor
- 64 MB of RAM
- CD-ROM Drive
- Printer with USB 1.1, USB 2.0, or Parallel Port
- Windows 98SE, Me, 2000 or XP

Package Contents

- Wireless-G PrintServer for USB 2.0
- Setup Wizard CD-ROM
- User Guide on CD-ROM
- USB 2.0 Cable
- Network Cable
- Power Supply
- Quick Installation
- Registration Card

Specifications are subject to change without notice. Linksys is a registered trademark or trademark of Cisco Systems, Inc. and/or its affiliates in the U.S. and certain other countries. Copyright © 2003 Cisco Systems, Inc. All rights reserved. Other brands and product names are trademarks or registered trademarks of their respective holders.